



MODEL NUMBER	DESCRIPTION
504-120-1	4" Vibrating bell, 120VAC
504WB-120	4" Vibrating bell, 120VAC, weatherproof back box
504WB-240	4" Vibrating bell, 240VAC, weatherproof back box
506-120-1	6" Vibrating bell, 120VAC
506WB-120	6" Vibrating bell, 120VAC, weatherproof back box
506WB-240	6" Vibrating bell, 240VAC, weatherproof back box

Vibratone® Bells
Models 504 & 506
(Fully Assembled Gong & Vibrating Mechanism)



504WB and 506WB pictured




SHORT SELLING STORY

VIBRATONE BELLS
ARE IDEAL FOR USE AS


- General Alarm
- Start & Dismissal
- Process Control Signaling in loud areas
- Harsh industrial environments
- Institutional applications

504
506



504 (Four inch gong)

- 120VAC or 240VAC
- Produces 98dB at 10 feet (107dB at 1 meter)
- Type 3R enclosure (protection against falling dirt, rain, sleet, snow, and windblown dust)
- UL and cUL Listed, CSA Certified, CSFM Approved
- *Model 504WB comes completely assembled with gong, mechanism, and backbox*



506 (Six inch gong)

- 120VAC or 240VAC
- Produces 100dB at 10 feet (109dB at 1 meter)
- Type 3R enclosure (protection against falling dirt, rain, sleet, snow, and windblown dust)
- UL & cUL Listed, CSA Certified, FM Approved
- *Model 506WB comes completely assembled with gong, mechanism, and backbox*

FEATURES

- Loudest bell on the market
- Heavy duty construction and powder coat
- Type 3R for indoor or outdoor
- Compact size but high audible performance

BENEFITS

- Clearly heard over distance or in high ambient noise situations
- Resists vandalism and the effects of harsh environments
- Suitable for outdoor applications
- Flexibility in application

APPLICATIONS

- Manufacturing
- Foundries
- Warehouses
- Process control
- Food processing

POSSIBLE CUSTOMERS

- OEM
- Panel builders
- MRO
- Systems integrators

COMPETITIVE ADVANTAGES

- Rugged construction
- Dependability
- Clarity of signal
- 5-year warranty

