









Selector Guide

Impulse/Latching Relays			PC Mount	
Series	R50	RLY76 & 77	R21	R22
				
Features	<ul style="list-style-type: none"> • Dust Cover • Magnetic Latching • .187" Quick Connect Terminals 	<ul style="list-style-type: none"> • Open Frame • Bistable • Pulse Operation • .250" Quick Connect Terminals 	<ul style="list-style-type: none"> • Subminiature Size • Epoxy Sealed • Class B 	<ul style="list-style-type: none"> • Dust Cover • Low Coil Power • Small Size • TV-5 Type
Contact Arrangement	SPDT, DPDT	DPDT	SPDT	SPST-NO, SPDT
Contact Ratings	10A @ 28VDC/120VAC	15A @ 28VDC/120VAC	1A, 2A @ 30VDC/125VAC	16A @ 30VDC/120VAC
Coil Voltage	120VAC 12, 24VDC	24, 120VAC 12, 24VDC	6, 12, 24VDC	3, 5/6, 12, 24, 48VDC
Nominal Coil Power AC Types DC Types	1.7VA 1.2W	9VA 6.5W	- 200, 360mW	- 540, 720mW
Options () Suffix	Dual Coil (C)			
Page	53	83	32	33

PC Mount (Cont'd)				
Series	R23	R24	R25	R40
				
Features	<ul style="list-style-type: none"> • Epoxy Sealed • Class B Insulation 	<ul style="list-style-type: none"> • Epoxy Sealed for Wave Soldering and Immersion Cleaning • Upright or Flat-Pack 	<ul style="list-style-type: none"> • Epoxy Sealed • Immersion Proof • Upright Package Type 	<ul style="list-style-type: none"> • Epoxy Sealed • Standard .100" DIP Terminal Spacing • Ultra-Sensitive Coil • Latching Type (Dual Coil Only)
Contact Arrangement	SPDT	SPDT	SPST-NO, SPDT, DPDT	DPDT, 4PDT
Contact Ratings	20A @ 24VDC/277VAC	8A, 10A @ 28VDC/120VA	10A, 16A @ 28VDC/120VAC	2A @ 28VDC/120VAC
Coil Voltage	6, 12, 24VDC	5/6, 6, 12, 24VDC	24, 120VAC 5/6, 12, 24, 48VDC	5/6, 12, 24, 48VDC
Nominal Coil Power AC Types DC Types	- 270mW	- 600mW	- 500mW	- 150, 180, 200, 300, 320mW
Options () Suffix		Upright Version (V) Flat-Pack Version (FP)		Dual Coil (C)
Page	34	35	36	45