









Selector Guide

Gen Purp Relays (Cont'd)		Power Relays		
Series	R55	R04	R18	R45
				
Features	<ul style="list-style-type: none"> • .250" Quick Connect Terminals • Flange Mount • Clear See-Thru Cover 	<ul style="list-style-type: none"> • Open Frame • Screw Terminals • Heavy Duty 	<ul style="list-style-type: none"> • Dust Cover • Jones Plug Terminals • Switches Tungsten Lamp Loads 	<ul style="list-style-type: none"> • Epoxy Sealed • Single-Pole Switching • .250" Quick Connect Terminals • Printed Circuit Terminals on Bottom
Contact Arrangement	SPDT, DPDT	SPST-NO, SPDT, DPST-NO, DPDT	DPDT	SPST-NO, SPDT
Contact Ratings	20A, 25A @ 28VDC/300VAC	30A @ 28VDC/120VAC	20A @ 28VDC/120VAC	20A, 30A @ 28VDC/300VAC
Coil Voltage	24, 120, 240VAC 12, 24VDC	12, 24, 120, 240VAC 12, 24, 110VDC	120VAC	5, 12, 24VDC
Nominal Coil Power AC Types DC Types	2.75, 3.0VA 1.2W	10VA 2.0W	4.0VA -	- 600mW, 900mW
Options () Suffix				Flange Mount (F)
Page	58	19-20	31	48

Power Relays (Cont'd)			Buzzers	
Series	R54	RLY16 & 17	RLY74 & 75	RB
				
Features	<ul style="list-style-type: none"> • Open Frame • .125" Quick Connect Terminals • Heavy Duty • 10A Tungsten Rating 	<ul style="list-style-type: none"> • Open Frame • Heavy Duty • Screw Terminals • Buzz-Free Shaded AC Coil 	<ul style="list-style-type: none"> • Heavy Duty • Multicontact • .250" Quick Connect Terminals 	<ul style="list-style-type: none"> • AC Operated • Lightweight • Audible Signal Source
Contact Arrangement	SPST-NO DM	4PDT	SPDT, DPDT	
Contact Ratings	30A @ 28VDC/120VDC	25A @ 277VAC 10A @ 28VDC	20A @ 277VAC	
Coil Voltage	24, 120, 240VAC 12, 24, 110VDC	24, 120, 240VAC 12, 24VDC	24, 120, 240VAC 12, 24VDC	12, 24, 120, 240VAC
Nominal Coil Power AC Types DC Types	3VA 1.5W	14VA 4.4W	4VA 3-4.5W	3VA -
Options () Suffix				
Page	57	79	82	111