








# Selector Guide

PC Mount (Cont'd)			
Series	R74	RLY34	RLY39
			
<b>Features</b>	<ul style="list-style-type: none"> <li>• Standard .100" PC Board Spacing</li> <li>• Low Power Consumption</li> </ul>	<ul style="list-style-type: none"> <li>• Sealed Construction</li> <li>• Rated for D 150 Pilot Duty</li> <li>• .100" Pin Spacing</li> </ul>	<ul style="list-style-type: none"> <li>• Epoxy Sealed</li> <li>• Immersion Proof</li> <li>• Low Profile</li> </ul>
<b>Contact Arrangement</b>	DPDT	SPST-NO	SPDT, DPDT
<b>Contact Ratings</b>	1A @ 30VDC	5A @ 30VDC/250VDC	2A @ 28VDC 1A @ 120VAC
<b>Coil Voltage</b>	3, 5, 6, 12, 24VDC	5, 12, 24VDC	5-6, 12, 24VDC
<b>Nominal Coil Power</b> AC Types DC Types	- 140, 200mW	- 200mW	- 600-860mW
<b>Options</b> ( ) Suffix	Surface Mount (SM)		
<b>Page</b>	78	80	81

Reed Relays				
Series	R42	R44	R56	R57
				
<b>Features</b>	<ul style="list-style-type: none"> <li>• .200" SIP Terminal Spacing</li> <li>• TTL Compatible</li> <li>• Internal Clamping Diode</li> </ul>	<ul style="list-style-type: none"> <li>• Standard .100" PC Board Spacing</li> <li>• TTL Compatible</li> </ul>	<ul style="list-style-type: none"> <li>• Standard .100" DIP Terminal Spacing</li> <li>• TTL Compatible</li> </ul>	<ul style="list-style-type: none"> <li>• Standard .100" DIP Terminal Spacing</li> <li>• TTL Compatible</li> </ul>
<b>Contact Arrangement</b>	SPST-NO	SPST-NO, DPST-NO	SPST-NO, SPDT, DPST-NO	SPST-NO, SPST-NC, SPDT
<b>Contact Ratings</b>	500mA @ 28VDC	5A Switching 2A Carry @ 200VDC	500mA @ 28VDC	250mA, 500mA @ 28VDC
<b>Coil Voltage</b>	5/6, 12, 24VDC	5/6, 12, 24VDC	5, 6, 12, 24VDC	5/6, 12, 24VDC
<b>Nominal Coil Power</b> AC Types DC Types	50, 77, 180mW	360, 510mW		
<b>Options</b> ( ) Suffix	330µs Operate Time	500µs Operate Time	Diode Protection (D)	Diode Protection (D)
<b>Page</b>	46	47	59-60	59-60